#### MATERIAL SAFETY DATA SHEET OSHA - Meets 29 CFR 1910.1200 Standards HMIS HAZARD RATINGS **HEALTH** 0 = INSIGNIFICANT 3 = HIGHn **FLAMMABILITY** 0 1 = SLIGHT 4 = EXTREMEREACTIVITY 0 2 = MODERATE TRANSPORTATION INFORMATION PROPER SHIPPING NAME: Not Regulated HAZARD CLASS / PKG GRP: None / None Not Applicable REF: **IDENTIFICATION NUMBER:** None LABEL: None Required SECTION 1 - PRODUCT / COMPANY IDENTIFICATION IDENTITY (AS USED ON LABEL AND LIST) Page 1 of 2 2541 SKYLIGHT SEALER MANUFACTURER'S NAME **EMERGENCY TELEPHONE NUMBER Insulating Coatings Corporation** CHEM • TEL (800) 255-3924 Outside USA (813) 248-0573 ADDRESS (NUMBER, STREET, P.O. BOX) TELEPHONE NUMBER FOR INFORMATION (800) 345-5306 956 South Hwy 41 (CITY, STATE AND ZIP CODE) DATE PREPARED: November 18, 2000 Inverness, FL 34450-SUPERSEDES: June 6, 1994 SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION HAZARDOUS COMPONENTS OSHA PEL **ACGIH TWA** % SARA RQ CAS# TITLE III (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S)) LBS (OPTIONAL) PPM MG/M<sup>3</sup> No hazardous materials present as defined in 29 CFR 1910.1000, 40 CFR 260 - 281, 302, 355, 370, 372 or WHMIS. SECTION 3 - HEALTH HAZARD DATA ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE EMERGENCY AND FIRST AID PROCEDURES INHALATION: None expected, however, certain individuals may be sensitized INHALATION: Remove affected person to fresh air; if symptoms persist seek and experience minor nausea or headaches. medical attention. SKIN: None expected, however, prolonged contact may cause irritation. SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention. EYES: Contact with eyes may cause irritation. EYES: Remove contact lenses. Flush eyes with water for 15 minutes; if irritation persists, seek medical attention. INGESTION: May cause gastric distress, vomiting and diarrhea. INGESTION: Give two glasses of water for dilution; DO NOT induce vomiting; seek medical attention. HEALTH HAZARDS (ACUTE AND CHRONIC): Acute effects are possible irritation and discomfort; no known chronic effects have been established. CARCINOGENICITY No IARC MONOGRAPHS? OSHA REGULATED? MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

#### MATERIAL SAFETY DATA SHEET

IDENTITY (AS USED ON LABEL AND LIST)

Page 2 of 2

FLAMMABLE LIMITS

Date: November 18, 2000

UEL: Not applicable

SECTION 4 - FIRE FIGHTING MEASURES

FLASH POINT (METHOD USED)

2541 SKYLIGHT SEALER

NFPA RATING

None LEL: Not applicable

Non-flammable

**EXTINGUISHING MEDIA** 

Carbon dioxide, water, water fog, dry chemical, chemical foam

SPECIAL FIRE FIGHTING PROCEDURES

Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

UNUSUAL FIRE AND EXPLOSION HAZARDS

None

### SECTION 5 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - soak up with approved absorbent, shovel product into approved container for disposal. Wash area with plenty of water.

### SECTION 6 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. Keep this and other chemicals out of reach of children.

## SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION (SPECIFY TYPE): None required.

VENTILATION	LOCAL EXHAUST:	Not necessary	SPECIAL:	None
	MECHANICAL (GENERAL):	Recommended	OTHER:	None

PROTECTIVE GLOVES: Recommended for general protection EYE PROTECTION: Recommended for general protection

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyebath nearby

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

## SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES

BOILING POINT	SPECIFIC GRAVITY (WATER = 1)
212º F	1.0 - 1.2
VAPOR PRESSURE (MM Hg)	VOLATILE ORGANIC COMPOUNDS (VOC's)
17 mm Hg @ 20 ° C	< 0.2 lbs / gallon
VAPOR DENSITY (AIR = 1)	EVAPORATION RATE (WATER = 1)
<1	Not applicable
SOLUBILITY IN WATER	% VOLATILE (BY WEIGHT)
Miscible	54% - 56%
APPEARANCE AND ODOR	pH
Milky white liquid, slight ammoniacal odor	Not determined

# SECTION 9 - STABILITY AND REACTIVITY

UNSTABLE: CONDITIONS TO AVOID: STABLE: XXX Extreme temperatures

INCOMPATIBILITY (MATERIALS TO AVOID):

Strong oxidizers, strong acids

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.

HAZARDOUS POLYMERIZATION MAY OCCUR: CONDITIONS TO AVOID:

WILL NOT OCCUR: XXX None

# SECTION 10 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Products classified as non - hazardous may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.

The information contained herein is believed to be accurate but is not warranted to be so. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed.